

## HARNES INSPECTION

Safety comes first ! At RoofSafeUK we only use the best equipment .

When it comes to safety PPE is very important

Our supplier for harness/lanyards/fall restraint lanyards all come from

Pammenter & Petrie Ltd - [www.pammenter.co.uk](http://www.pammenter.co.uk)

### LANYARDS RL150 ADJ - EN354, EN358

A lanyard (Safety Line) is used to connect a safety harness, work position or restraint belt to an anchorage point to hold the user in a supported work position or to prevent the user reaching a position where a severe fall is possible. (Used in the cherry picker's MEWPS)



### LANYARDS NRG200 SCA - EN355

This type of lanyard is an energy absorbing lanyard and is used to connect a safety harness to an anchorage point and, in the event of a fall, limit the force applied to a user's body to a maximum of 6KN.



### BRITANNIA FRS (FALL ARREST HARNESS) - EN361

The FRS has a full chest strap with shoulder, chest and leg strap adjustments. In a work application where there is a fall potential full body harness Must be worn.. This will, give the wearer the greatest protection with virtually all the forces applied being absorbed by the thighs and the buttocks and retaining the wearer in a near upright position.

ALL OUR HARNESS AND LANYARDS COME WITH A CERTIFICATE OF CONFORMITY.

The recommended life of p&p fall protection and rescue equipment manufactured in webbing and / or rope is 5 years in use. This is providing they are used, inspected, maintained and stored in accordance with the product fitting / user instructions and provided user manual.

We have received training and completed a course to inspect our own harness/lanyards from The Access Group . [www.the-access-group.com](http://www.the-access-group.com)

We inspect all our workers harness/lanyards at regular intervals, not exceeding every 3months. any defects found however small the equipment will be scrapped and taken out of service.

Although the equipment has a recommended life of 5 years in use, we SCRAP all equipment after 1 year